

Annex 2

Product technical sheet Prana 210G Serie				
Supplier		PRANA PLATINUM LLC.		
Model		210G BASE m23 (Clock control) 210G ERP m23 (Local demand control) 210G ERP PRO m23 (Local demand control)		
Climate zone	Type of control	SEC [kWh/m ² a]	AEC [kWh/a]	AHS [kWh/a]
Average	Clock control	-29,71 (B)	2,13	34,36
	Local demand	-36,57 (A)	1,24	38,90
Cold	Clock control	-57,20 (A+)	7,50	67,21
	Local demand	-68,48 (A+)	6,61	76,26
Warm	Clock control	-11,34 (E)	1,68	15,54
	Local demand	-17,63 (E)	0,79	17,63
Typology		BVU		
Type of drive installed		Variable speed drive		
Type of heat recovery system		Recuperative		
Maximum thermal efficiency of heat recovery [%]		95		
Maximum flow rate [m ³ /h]		65		
Electric power input at maximum flow rate [W]		18,5		
Maximum sound power level [dB(A)]		50		
SPI [W/m ³ /h]		0,13		
Control factor	Clock control	0,95		
	Local demand control	0,65		
Internal/external leakage rate [%]		0,6/6,1		
Airflow sensitivity class		S3		
Indoor and outdoor air tightness class		D3		
Position of visual filter warning		Mobile application/Front display		

*Heat recovery mode at Speed 1_5,5 m³/h according to EN 13141-8:2014 +7°C/+20°C